











National Emission Standards for Hazardous Air Pollutants for Reciprocating Internal Combustion Engines (RICE Rule)



40 CFR 63 Subpart ZZZZ

Major New Emergency Engine ≤500 Horsepower

(except 4-Stroke Lean Burn Engines ≥250 Horsepower)



Continuous Compliance Requirements

Engines **must** meet all applicable NSPS requirements and state emergency engine requirements.







NSPS Emergency Engine Requirements

- No limits on hours of operation for emergency service
- 100 hours/year allowed for:
 - Maintenance and testing
 - Emergency demand response for periods in which the Reliability Coordinator under the North American Electric Reliability Corporation Reliability Standard EOP-002-3, Capacity and Energy Emergencies, or other authorized entity as determined by the Reliability Coordinator, has declared an Energy Emergency Alert Level 2.; and
 - Responding to situations when there is at least a 5% or more change in voltage or frequency.
 - 50 of the 100 hours can be used for non-emergency purposes
 - 50 hours can be used for peak shaving or non-emergency demand response, or to generate income for a facility to an electric grid or otherwise supply power as part of a financial arrangement if <u>all</u> of the following conditions are met:
 - Engine is dispatched by the local balancing authority or local transmission and distribution system operator
 - Dispatch is intended to mitigate local transmissions and/or distribution limitations so as to avert potential voltage collapse or line overloads that could lead to the interruption of power supply in a local area or region
 - Dispatch follows reliability, emergency operation or similar protocols that follow specified North American Electric Reliability Corporation (NERC), regional, state, public utility commission or local standards or guidelines
 - Power is provided only to the facility itself or to support the local transmission and distribution system.
 - Owner/operator identifies and records the entity that dispatches the engine and the specific NERC, regional, state, public utility commission or local standards or guidelines that are being followed for dispatching the engine. The local balancing authority or local transmission and distribution system operator may keep these records on behalf of the engine owner/operator.



Emergency Engine Requirements

- If an emergency engine operates for more than allowable hours for non-emergency purposes, it will
 need to meet all non-emergency engine requirements.
- If engine is located in CT, also comply with CT emergency engine requirements
- If located elsewhere, comply with State emergency engine requirements







NSPS Emergency Engine Requirements

- •Starting in 2015, if you operate or commit to operate >15 hours annually as part of blackout and brownout prevention, also known as emergency demand response, or for local reliability, and your engine is >100 HP:
 - Collect and submit an annual report including location, dates and times of operation.
 - •First report must cover calendar year 2015 and is due March 31, 2016.
 - •Submit electronically using the form in the Compliance and Emissions Data Reporting Interface that is accessed through EPA's Central Data Exchange at www.epa.gov/cdx.





CT Emergency Engine Requirements

According to Sec. 22a-174-22(a)(3) of the RCSA, "emergency engine" means a stationary reciprocating engine or a turbine engine which:

- •Provides mechanical/electrical power only during periods of
 - -testing and scheduled maintenance or
 - -during an emergency or
 - -in accordance with a contract ensuring electricity for use within the state of CT during an OP-4, Step 6 event
- •Does <u>not</u> include an engine for which the owner/operator is party to any other agreement to sell electrical power from such engine to an electricity supplier, or otherwise receives any reduction in the cost of electrical power for agreeing to produce power during periods of reduced voltage or reduced power availability.

Note: Engines operating under RCSA Sections 22a-174-3b and 3c must comply with additional requirements



Emergency Engine Requirements

Federal Only	Common to Both	State Only
 100 hr/yr limit: Testing and maintenance checks Readiness testing Emergency demand response Responding to a 5% or more change in voltage 50 hr/yr of the 100 hr/yr limit: Non-emergencies if no financial arrangement Can only be used as part of a financial arrangement if specific conditions are met 	 Emergency hrs of operation: no limit (unless subject to 22a-174-3b or 3c) Engine cannot be used as part of any other agreement or financial arrangement with another entity 	 Only operate during emergencies, maintenance/scheduled testing, or during an OP-4, Step 6 event If operating under RCSA Sec. 22a-174-3b: Emergency hrs of operation: 300 hr/yr limit Any nongaseous fuel consumed by engine shall not exceed sulfur content of 0.0015%, dry basis If operating under RCSA Sec. 22a-174-3c: No restriction on hrs of use or fuel sulfur content, however total facility purchases of fuel are extremely limited



You are subject to the CI NSPS (40 CFR 60 Subpart IIII) if your emergency CI engine was:

-Constructed (ordered*) after July 11, 2005 AND manufactured after April 1, 2006 (July 1, 2006 for fire pump engines)

OR

-Modified/reconstructed after July 11, 2005





*NOTE: For the purposes of this rule, the date that construction commences is the date the engine is ordered by the owner or operator.

If you are subject to the CI NSPS, you must meet these requirements:

Emission and Operating Limits, Testing Requirements, Monitoring Requirements:

- See Table
- •Must meet these standards for the life of the engine

Fuel Requirements:

- •As of October 1, 2007 500 ppm sulfur diesel (LSD)
- •As of October 1, 2010 15 ppm sulfur diesel (ULSD) for engines <30 l/cyl displacement
 - -You may use up any diesel fuel acquired prior to October 1, 2010 that does not meet the requirements for nonroad diesel fuel.
- •As of June 1, 2012 1,000 ppm sulfur diesel for engines ≥30 l/cyl displacement
 - -Per 40 CFR 60.4215(b), ICE used in Guam, American Samoa, or the Commonwealth of the Northern Mariana Islands are not required to meet fuel requirements.
 - -Per 40 CFR 60.4217, ICE that do not use diesel fuel may petition EPA for approval of alternative emission standards, if they can demonstrate that they use a fuel that is not the fuel on which the manufacturer of the engine certified the engine and that the engine cannot meet the applicable standards required in 40 CFR 60.4204 or 60.4205 using such fuels and that use of such fuel is appropriate and reasonably necessary, considering cost, energy, technical feasibility, human health and environmental, and other factors, for the operation of the engine.



If you are subject to the CI NSPS, you must meet these requirements:

Compliance Requirements:

- •If you have 2007 model year or later engine with displacement <30 l/cyl, or a fire pump engine that is 2008-2011 model year or later, depending on engine size, you must:
 - Purchase certified engine
 - •Install, configure, operate and maintain engine per manufacturer's instructions/procedures
 - -Performance testing not required
 - -Can operate differently than manufacturer's recommendations, but must then do performance test to show compliance
- •Engines not required to be certified (Choose one of the following to demonstrate compliance):
 - Purchase certified engine
 - •Keep records of performance test conducted on similar engine
 - •Keep records of engine manufacturer data indicating compliance
 - •Keep records of control device vendor data indicating compliance
 - Conduct initial performance test
- •Engines ≥30 I/cyl displacement:
 - Initial performance test
 - Continuously monitor operating parameters



Recordkeeping/Reporting:

- Install non-resettable hour meter and keep records of operation
- Engine equipped with diesel particulate filter (DPF)
 - -Backpressure monitor and records of corrective actions





Emergency CI Engine Category	Date Constructed/ Reconstructed/ Manufactured	Emission Standards ^{a,b,c,d}	Importing/ Installing Requirements	Compliance Requirements	Testing Requirements	General Provisions (40 CFR part 60)
Pre-2007 model year <10 l/cyl (except fire pump engines)	Commenced construction	60.4205(a) Table 1	60.4208(a), (b), (h), (i)	60.4211(a), (b), (f), (g)	60.4212	Table 8
Pre-2007 model year 10 l/cyl≤displacement<30 l/cyl (except fire pump engines)	after 7/11/2005 and manufactured after 4/1/2006	60.4205(a) 40 CFR 94.8(a)(1)				
2007 model year and later <30 l/cyl (except fire pump engines)		60.4205(b) 60.4202		60.4211(a), (c), (f), (g)		
Fire pump engines <30 l/cyl manufactured prior to the model years in Table 3 of 40 CFR part 60, subpart IIII	Commenced construction after 7/11/2005 and	60.4205(c) Table 4	60.4208(h), (i)	60.4211(a), (b), (f), (g)		
Fire pump engines <30 l/cyl manufactured during or after the model year that applies to your fire pump engine power rating in Table 3 of 40 CFR part 60, subpart IIII				60.4211(a), (c), (f), (g)		
≥30 l/cyl (except fire pump engines)	Commenced construction after 7/11/2005 and manufactured after 4/1/2006	60.4205(d)(1) and (2)	60.4208(a), (b), (h), (i)	60.4211(a), (d), (f), (g)	60.4213	
Modified/Reconstructed <30 l/cyl	Pre-2007 Model Year: 60.4205(a) Modified or reconstructed after 7/11/2005 Later: 60.4205(b)		60.4208(i)	60.4211(a), (e), (f), (g)	60.4212 60.4204(e)	
Modified/Reconstructed		60.4205(d)(1)-(3)			60.4213	

^aPer 60.4200(e), facilities with ICE that are acting as temporary replacement units and that are located at a stationary source for <1 year and that have been properly certified as meeting the standards that would be applicable to such engine under the appropriate nonroad engine provisions, are not required to meet any other provisions under this rule with regard to such engines' requirements in 40 CFR 60.4207.

standards in \$60.4202 and \$60.4205.

^c ICE with a displacement of ≥30 l/cyl that are used in Guam, American Samoa, or the Commonwealth of the Northern Mariana Islands are required to meet the emission standards in 60.4215(c).

^dSpecial requirements apply to engines used in Alaska. Please refer to 60.4216 for the specific requirements that apply.



≥30 l/cyl

CFR 60.4207.

bPer 60.4215(a), ICE with a displacement of <30 l/cyl that are used in Guam, American Samoa, or the Commonwealth of the Northern Mariana Islands are required to meet the applicable emission

Spark Ignition New Source Performance Standards (SI NSPS)

You are subject to the SI NSPS (40 CFR 60 Subpart JJJJ) if your emergency SI engine was:

—Constructed (ordered*) after June 12, 2006 AND either: >25 HP manufactured on/after January 1, 2009 or ≤25 HP and manufactured on/after July 1, 2008

OR

-Modified/reconstructed after June 12, 2006.

*NOTE: For the purposes of this rule, the date that construction commences is the date the engine is ordered by the owner or operator.



Spark Ignition New Source Performance Standards (SI NSPS)

If you are subject to the SI NSPS, you must meet these requirements:

- •Emission and Operating Limits, Testing Requirements, Monitoring Requirements:
 - See Table
 - •Must meet these standards for the life of the engine
- •Fuel Requirements:
 - •Gasoline engines must use gas that meets the sulfur limit: cap of 80 ppm/gal



Spark Ignition New Source Performance Standards (SI NSPS)

If you are subject to the SI NSPS, you must meet these requirements:

Compliance Requirements:

If you have a certified engine:

- •Install, configure, operate and maintain engine according to manufacturer's instructions
- •If you do not operate/maintain according to manufacturer's instructions for engines ≥100 HP-
 - -Keep maintenance plan and maintenance records, operate consistent with good air pollution control practices
 - -Initial performance test and retest if engine is rebuilt or undergoes major repair or maintenance

If you have a *non-certified* engine >25 HP:


- Maintenance plan
- •Initial performance test and retest if engine is rebuilt or undergoes major repair or maintenance


•Recordkeeping/Reporting:

- •Install non-resettable hour meter if:
 - -500 HP built on/after July 1, 2010
 - ≥130 HP built on/after January 1, 2011 or
 - -<130 HP built on/after July 1, 2008
- Documentation of certification (EPA Certificate of Conformity)
- •Records of engine maintenance
- •Record hours of operation
- •Initial notification for non-certified engines if HP=500
- •Notification of Intent to Conduct Performance Testing 30 days prior to test
- •Results of performance testing within 60 days of test



Engine Certification







EPA Certificate of Conformity



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY 2012 MODEL YEAR CERTIFICATE OF CONFORMITY WITH THE CLEAN AIR ACT OF 1990

OFFICE OF TRANSPORTATION AND AIR QUALITY ANN ARBOR, MICHIGAN 48105

Certificate Issued To: Generac Power Systems, Inc.

(U.S. Manufacturer or importer)

Certificate Number: CGNXB06.82NN-012

Effective Date: 10/26/2011

Expiration Date: 12/31/2012 Byron J. Burker, Acting Division Director

Issue Date: 10/26/2011

Revision Date:

Manufacturer: Generac Power Systems, Inc.

Engine Family: CGNXB06.82NN

Certificate Number: CGNXB06.82NN-012 Certification Type: Stationary (Part 60) Fuel: Natural Gas (CNG/LNG)

Emission Standards: NMHC + NOx (g/kW-hr): 13.4

CO (g/kW-hr): 519 HC + NOx (g/kW-hr): 13.4

Emergency Use Only: Y

Pursuant to Section 213 of the Clean Air Act (42 U.S.C. section 7547) and 40 CFR Part 60, 1065, 1068, and 60 (stationary only and combined stationary and mobile) and subject to the terms and conditions prescribed in those provisions, this certificate of conformity is hereby issued with respect to the test engines which have been found to conform to applicable requirements and which represent the following nonroad engines, by engine family, more fully described in the documentation required by 40 CFR Part 50 and produced in the stated model year.

This certificate of conformity covers only those new nonroad spark-ignition engines which conform in all material respects to the design specifications that applied to those engines described in the documentation required by 40 CFR Part 60 and which are produced during the model year stated on this certificate of the said manufacturer, as defined in 40 CFR Part 60. This certificate of conformity does not cover nonroad engines imported prior to the effective date of the certificate.

It is a term of this certificate that the manufacturer shall consent to all inspections described in 40 CFR 1068.20 and authorized in a warrant or court order. Failure to comply with the requirements of such a warrant or court order may lead to revocation or suspension of this certificate for reasons specified in 40 CFR Part 60. It is also a term of this certificate that this certificate may be revoked or suspended or rendered void ab initio for other reasons specified in 40 CFR Part 60.

This certificate does not cover large nonroad engines sold, offered for sale, or introduced, or delivered for introduction, into commerce in the U.S. prior to the effective date of the certificate.

SI ICE >25 HP		>25 HP Gasoline >25 HP Rich Burn LPG	60.4231(b) 60.4233(b) 60.4231(c) 60.4233(c)	built on of after 7/1/2008 60.4236(c) 7/1/2008 or 130≤HP< 00 built of after 1/1/2011 or =500		If using AFRC: 60.4243(g) 40 CFR part 1068, subparts A-D.	None		<100 HP : None 100≤HP : 60.4243(a)(2)(ii) ⁵⁶ 60.4244	60.4245(a), (b), (e)	
	Manufactur ed on or after 1/1/2009	25 <hp<100 (except gasoline and rich burn LPG)</hp<100 	60.4233(d) ⁴			If using AFRC: 60.4243(g) Certified:	All Engines: If natural gas engine and using propane as alternative fuel for >100 hrs/yr: 60.4243(e) Non-Certified: 60.4243(b)(2)(i) ⁵ , 60.4244	60.4243(g)	Certified: None Non-Certified: Non-Certified > 25: 60.4244 25>HP: 60.4243(b)(2)(i) ⁵ All Engines: If natural gas engine and using propane as alternative fuel for >100 hrs/yr: 60.4243(e)	to the following of the	60.4246 Table 3
		≥100 HP (except gasoline and rich burn LPG)	60.4233(e) ⁵ Table 1		130≤HP<5 00 built on	2008, or \$\left\{ \text{60.4243(b)(1)}} \\ \text{Non-certified:} \\ \text{60.4243(b)(2)} \\ \text{ill t on after} \\ \text{2011,} \\ = 500 \end{array}			All Engines: If natural gas engine and using propane as alternative fuel for >100 hrs/yr: 60.4243(e) Certified: Engines ≥100 HP: 60.4244 100≤HP: 60.4243(a)(2)(ii) Non-Certified: Engines >25 HP: 60.4244 25>HP: 60.4243(b)(2)(i) ⁵		
Modifie d/Recon red structed	reconstruct > ed after 6/12/2006 >25	≤25 HP	60.4233(f)(1)	None None	on or after 7/1/2010: 60.4237		60.4245(a), (b), (e)				
		>25 HP Gasoline	60.4233(f)(2)								
		>25 HP Rich Burn LPG	60.4233(f)(3)		If using AFRC: 60.4243(g) 60.4243(i)		60.4245(a), (b),				
		>25 HP SI natural gas and lean burn LPG	60.4233(f)(4)				(d), (e)				
		>25 HP Landfill/Digester Gas									
engine un ² If you op ³ If you do ⁴ Owners/o maximum	der the apprerate and mand operate operators of a power $\geq 10^{\circ}$	opriate nonroad enging intain the certified en and maintain the certified with a maximum of HP and <500 HP, maximum of HP and <500 HP and <50	e provisions, ar gine and contro ified engine and power >19 KV ay optionally cl	e not required of device accord control device V (25 HP) and noose to meet	to meet any rding to the e according l <75 KW (those stand	y other provisions und manufacturer's emiss g to manufacturer's en 100 HP) manufacture ards.	der the rule with reg sion-related instruct nission-related instr d prior to January 1	gard to such engi- ions, you are oper ructions, your eng , 2011, that were	n properly certified as meeting the standards that would nes. erating in a certified manner. gine will be considered a non-certified engine. e certified to the standards in Table 1 to the rule applica curer's emission-related instructions, you are required to	able to engines with	

Engines being operated and

maintained in a certified manner²

Performance

Testing

General

Compliance

Importing/

Installing

Reqs⁶

Monitorin

g Reqs

Emission

Standards

Compliance Requirements

General

Compliance

Engines being operated and maintained in a non-certified manner

Performance Testing

Date

Constructe

Reconstru

cted/

Manufactu

red

Category

Size/Engine

Type/Fuel

been rebuilt as that term is defined in 40 CFR 94.11(a).

Connecticut Department of Energy and Environmental Protection

performance testing as indicated in this table, but you are not required to conduct subsequent performance testing unless the engine is rebuilt or undergoes major repair or maintenance. A rebuilt ICE means an engine that has

The requirements of this section do not apply to ICE that have been modified or reconstructed, and they do not apply to engines that were removed from one existing location and reinstalled at a new location.

General

Provision

(40 CFR

part 60)

Notification,

Reports, and

Records

Requirements

By when must I comply with the rule?

Upon startup



Photo credit: EPA



Where do I send notifications and reports?

Unless otherwise specified, send reports to:



EPA REGION 1:

US Environmental Protection Agency
5 Post Office Square, Suite 100, Mail code: OES04-2

Boston, MA 02109-3912


Attention: Air Clerk



Visit the EPA RICE Compliance Page

www.epa.gov/ttn/atw/icengines

- Fact sheets
- Regulations
- Example notifications
- Announcements
- Q & A documents
- Testing advice
- Recorded webinars
- ...and more!





Take Aways

Engine Type:

•A new or reconstructed emergency engine at a major source having a site rating of less than or equal to 500 horsepower

Compliance Requirements:

•Must meet all applicable NSPS requirements and State emergency engine requirements.

CT Emergency Engine Requirements

- •Emergency hrs of operation: no limit (unless subject to 22a-174-3b or 3c)
- •Engine cannot be used as part of any other agreement or financial arrangement with another entity
- •Only operate during emergencies, maintenance/scheduled testing, or during an OP-4, Step 6 event

If operating under RCSA Sec. 22a-174-3b:

- -Emergency hrs of operation: 300 hr/yr limit
- -Any nongaseous fuel consumed by engine shall not exceed sulfur content of 0.0015%, dry basis

If operating under RCSA Sec. 22a-174-3c:

-No restriction on hrs of use or fuel sulfur content, however total facility purchases of fuel are extremely limited



Take Aways

NSPS:

- Comply with CI or SI NSPS, if applicable
- •NSPS emergency engine requirements:
 - oEmergency hours of operation: no limit
 - o100 hours/year allowed for:
 - Maintenance checks and readiness testing
 - •Demand response for Energy Emergency Alert Level 2 situations; and
 - •Responding to situations when there is at least a 5% or more change in voltage.
 - •50 of the 100 hours can be used for non-emergency situations
 - •Cannot be used for peak shaving, non-emergency demand response, or to supply power as part of a financial arrangement with another entity *unless* engine meets <u>all</u> specified requirements
 - olf you operate or commit to operate >15 hours annually as part of emergency demand response, submit annual report
 - •First report must cover calendar year 2015 and is due March 31, 2016.
- •If an emergency engine operates for more than allowable hours for non-emergency purposes, it will need to meet all non-emergency engine requirements.

Compliance Date:

Upon startup

